

TS-431X2-2G	
CPU	AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor
CPU Architecture	32-bit ARM
Floating Point Unit	Yes
Encryption Engine	Yes
System Memory	2 GB SODIMM DDR3 RAM
Maximum Memory	8
Memory Slot	1
Flash Memory	512 MB (Dual boot OS protection)
Drive Bay	4 x 2.5"/3.5" SATA 6Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	2
10 Gigabit Ethernet Port	1 x 10G SFP+
Jumbo Frame	Yes
USB 3.0 port	3
Form Factor	Tower
LED Indicators	Power, Status, LAN, USB, HDD1-4
Buttons	Power, Reset, USB Auto Copy
Dimensions (HxWxD)	169 × 160 × 219 mm
Weight (Net)	2.03 kg
Weight (Gross)	3.46 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	External Power Adapter,90W, 100-240V
Power Consumption: HDD Sleep Mode	11.32 W

Power Consumption: Operating Mode, Typical	26.19 W With drives fully populated
Fan	1 x 12cm smart Fan (12V DC)
Sound Level	19.5 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.